

A519 GRADE 1020 CARBON STEEL

Datasheet for A519 Grade 1020 Carbon Steel

- Pipes & Tubes
- Sheets & Plates
- Bars & Rods, Forgings
- Fittings & Flanges
- Nuts & Bolts
- Valves



WWW.STEELPIPESFACTORY.COM – METALLICA METALS

We are a metal supplier of Hastelloy, Monel, Inconel, Incoloy, Stainless Steel, Duplex, Super Duplex, Nickel Alloys and more. Email: info@metallicametals.com | Tel: +91 8928722715 | +91-22-66581538, +91-22-67436694, +91-22-66109768

Datasheet for Carbon Steel A519 Grade 1020

What is Carbon Steel A519?

Carbon steel is a steel with carbon content up to 2.1% by weight. The definition of carbon steel from the American Iron and Steel Institute (AISI) states: Steel is considered to be carbon steel when: no minimum content is specified or required for chromium, cobalt, molybdenum, nickel, niobium, titanium, tungsten, vanadium or zirconium, or any other element to be added to obtain a desired alloying effect; the specified minimum for copper does not exceed 0.40 percent; or the maximum content specified for any of the following elements does not exceed the percentages noted: manganese 1.65, silicon 0.60, copper 0.60.

The term "carbon steel" may also be used in reference to steel which is not stainless steel; in this use carbon steel may include alloy steels.

As the carbon percentage content rises, steel has the ability to become harder and stronger through heat treating; however, it becomes less ductile. Regardless of the heat treatment, a higher carbon content reduces weldability. In carbon steels, the higher carbon content lowers the melting point.

Carbon Steel A519 Grade 1020 Product Specification

Product	ASTM A519 Grade 1020 Seamless Carbon and Alloy Mechanical Tubing	
Specification	seamless Carbon and Alloy Mechanical Tubing	
Туре	Seamless	
Size	15.9mm to 323.8mm	
Thickness	3.5mm to 12.7mm	
Length	6000mm, 12000m, Single Random Length, Double Random Length, or as customer's requirement.	
Grades	1020	
Test Certificates	Material Test Certificates (MTC) as per EN 10204 3.1 and EN 10204 3.2	
Coating	Tubing shall be coated with a film of oil before shaping to retard rust. tubing may be coated with a rust retarding oil on the outside and inside surfaces, at the option of the manufacturer.	

Annearance	The tubing shall be free of laps, cracks, seams, and other defects as is consistent with good commercial practice. The surface finish will be compatible with the condition to which it is ordered.
Applications	Mechanical engineering, mechanical and pressure use, and also for transporting steam, water, gas, etc.

Difference Between Carbon Steel and Stainless Steel

Carbon steel and stainless steel have the same basic ingredients of iron and carbon. Their main difference is alloy content—carbon steel has under 10.5 percent alloy content, while stainless steel must contain 10.5 percent chromium or more. That essential difference is what gives carbon steel and stainless steel their distinct physical characteristics.

Carbon Steel	Stainless Steel
Vulnerable to rust	Resistant to rust
Brittle	Less Brittle
Wear-resistant	Less wear-resistant

Types of Carbon Steel

- 1. Low carbon steel Carbon content 0.55-1.05%
- 2. Medium carbon steel- Carbon content 0.25-10.6%
- 3. High carbon steel- Carbon content 0.9-2.5%
- 4. Super High carbon steel- Carbon content 2.5-3.0%

Commonly used Carbon Steel explained below:

1. Low Carbon Steel

• Plain carbon steels - very low content of alloying elements and small amounts of Mn.

- Most abundant grade of steel is low carbon steel greatest quantity produced; least expensive.
- Not responsive to heat treatment; cold working needed to improve the strength.
- Good Weldability and machinability.
- High Strength, Low Alloy (HSLA) steels alloying elements (like Cu, V, Ni and Mo) up to 10 wt %; have higher strengths and may be heat treated.

2. Medium Carbon Steel

- Carbon content in the range of 0.3 0.6%.
- Can be heat treated austenitizing, quenching and then tempering.
- Most often used in tempered condition tempered martensite.
- Medium carbon steels have low hardenability.
- Addition of Cr, Ni, Mo improves the heat treating capacity.
- Heat treated alloys are stronger but have lower ductility.
- Typical applications Railway wheels and tracks, gears, crankshafts.

3. High Carbon Steel

- High carbon steels Carbon content 0.6 1.4%.
- High C content provides high hardness and strength.
- Hardest and least ductile.
- Used in hardened and tempered condition.
- Strong carbide formers like Cr, V, W are added as alloying elements to from carbides of these metals.
- Used as tool and die steels owing to the high hardness and wear resistance property.

4. Super High Carbon Steel

- Approximately 1.25–2.0% carbon content.
- Steels that can be tempered to great hardness.
- Used for special purposes like (non-industrial-purpose) knives, axles or punches.
- Most steels with more than 2.5% carbon content are made using powder metallurgy.

Application of Carbon Steel

Carbon steel is used in boilers, pressure vessels, heat exchangers, piping, and other moderate-temperature service systems in which good strength and ductility are desired. Significant other factors include cost, availability, and the ease of fabrication.

Effects of Alloying Elements on Steel

- •Manganese strength and hardness; decreases ductility and weldability; effects hardenability of steel.
- Phosphorus increases strength and hardness and decreases ductility and notch impact toughness of steel.
- •Sulfur decreases ductility and notch impact toughness Weldability decreases. Found in the form of sulfide inclusions.
- •Silicon one of the principal deoxidizers used in steel making. In low-carbon steels, silicon is generally detrimental to surface quality.
- •Copper detrimental to hot-working steels; beneficial to corrosion resistance (Cu>0.20%).
- •Nickel ferrite strengthener; increases the hardenability and impact strength of steels.
- •Molybdenum increases the hardenability; enhances the creep resistance of low-alloy steels.

Frequently Used ASTM Grades of Carbon Steel

Carbon Steel	Туре	Standard	Grades	Specification
Medium-Temp	Pipes	A106	A, B, C	This specification covers carbon steel pipe for high-temperature service.
	Fittings	A234	WPA, WPB, WPC	This specification covers wrought carbon steel and alloy steel fittings of seamless and welded construction.
	Flanges	A105		This specification covers standards for forged carbon steel piping components, that is, flanges, fittings, Valves, and similar parts, for use in pressure systems at ambient and higher-temperature service conditions.
	Valves	A216	WCB	This specification covers carbon steel castings for Valves, flanges, fittings, or other pressure-containing parts for high-temperature service and of quality suitable for assembly with other castings or wrought-steel parts by fusion welding.
	Bolts & Nuts	A193	B7	This specification covers alloy and stainless steel bolting material for pressure vessels, Valves, flanges, and fittings for high temperature or high pressure service, or other special purpose applications.

		A194	2H	Standard specification for nuts in many different material types.
High-Temp	Pipes	A335	P1, P11, P12, P22, P5, P9	This specification covers seamless ferritic alloy-steel pipe for high-temperature service.
	Fittings	A234	WP1, WP11, WP12, WP22, WP5, WP9	This specification covers wrought carbon steel and alloy steel fittings of seamless and welded construction.
	Flanges	A182	F1, F11, F12, F22, F5, F9	This specification covers forged or rolled alloy and stainless steel pipe flanges, forged fittings, and Valves and parts for high-temperature service.
	Valves	A217	WC1, WC6, WC9, C5, C12	This specification covers steel castings, martensitic stainless steel and alloys steel castings for Valves, flanges, fittings, and other pressure-containing parts intended primarily for high-temperature and corrosive service.
	Bolts & Nuts	A193	В7	This specification covers alloy and stainless steel bolting material for pressure vessels, Valves, flanges, and fittings for high temperature or high pressure service, or other special purpose applications.
		A194	2H	Standard specification for nuts in many different material types.
Low-Temp	Pipes	A333	6, 3	This specification covers wall seamless and welded carbon and alloy steel pipe intended for use at low temperatures.
	Fittings	A420	WPL6, WPL3	Standard specification for piping fittings of wrought carbon steel and alloy steel for low-temperature service.
	Flanges	A182	F304, F316, F321, F347	This specification covers forged or rolled alloy and stainless steel pipe flanges, forged fittings, and Valves and parts for high-temperature service.
	Valves	A182	F304, F316, F321, F347	This specification covers forged or rolled alloy and stainless steel pipe flanges, forged fittings, and Valves and parts for high-temperature service.
	Bolts & Nuts	A193	B8	This specification covers alloy and stainless steel bolting material for pressure vessels, Valves, flanges, and fittings for high temperature or high pressure service, or other special purpose applications.

A1	194	8	Standard specification for nuts in many different material types.
----	-----	---	---

Heat Treatment

The purpose of heat treating carbon steel is to change the mechanical properties of steel, usually ductility, hardness, yield strength, or impact resistance. Note that the electrical and thermal conductivity are only slightly altered. As with most strengthening techniques for steel, Young's modulus (elasticity) is unaffected. All treatments of steel trade ductility for increased strength and vice versa. Iron has a higher solubility for carbon in the austenite phase; therefore, all heat treatments, except spheroidizing and process annealing, start by heating the steel to a temperature at which the austenitic phase can exist. The steel is then quenched (heat drawn out) at a moderate to low rate allowing carbon to diffuse out of the austenite forming iron-carbide (cementite) and leaving ferrite, or at a high rate, trapping the carbon within the iron thus forming martensite. The rate at which the steel is cooled through the eutectoid temperature (about 727°C) affects the rate at which carbon diffuses out of austenite and forms cementite. Generally speaking, cooling swiftly will leave iron carbide finely dispersed and produce a fine grained pearlite and cooling slowly will give a coarser pearlite. Cooling a hypoeutectoid steel (less than 0.77 wt% C) results in a lamellar-pearlitic structure of iron carbide layers with α -ferrite (nearly pure iron) between. If it is hypereutectoid steel (more than 0.77 wt% C) then the structure is full pearlite with small grains (larger than the pearlite lamella) of cementite formed on the grain boundaries. A eutectoid steel (0.77% carbon) will have a pearlite structure throughout the grains with no cementite at the boundaries. The relative amounts of constituents are found using the lever rule. The following is a list of the types of heat treatments possible:

- 1. Spheroidizing5
- 2. Full annealing
- 3. Process annealing
- 4. Isothermal annealing
- 5. Normalizing
- 6. Quenching
- 7. Martempering (Marquenching)
- 8. Tempering
- 9. Austempering

Forging Temperature of Steel

Steel Type	Maximum forging temperature (°F / °C)	Burning temperature (°F / °C)
1.5% carbon	1920 / 1049	2080 / 1140
1.1% carbon	1980 / 1082	2140 / 1171

2050 / 1121	2230 / 1221
2280 / 1249	2460 / 1349
2410 / 1321	2680 / 1471
2280 / 1249	2500 / 1371
2280 / 1249	2500 / 1371
2320 / 1271	2640 / 1449
2280 / 1249	2460 / 1349
2370 / 1299	2520 / 1385
2340 / 1282	2520 / 1385
2370 / 1299	2590 / 1420
2280 / 1249	2460 / 1350
	2280 / 1249 2410 / 1321 2280 / 1249 2280 / 1249 2320 / 1271 2280 / 1249 2370 / 1299 2370 / 1299

Chemical Composition of ASTM A519 Grade 1020 Carbon and Alloy Steel Mechanical Tubes

Chemical Requirements of Carbon Steels				
Grade	Chemical Composition Limits, %			
Designation	С	Mn	P, max	S, max
1020	0.18-0.23	0.30-0.60	0.040	0.050

Mechanical Properties of ASTM A519 Grade 1020 Carbon and Alloy Steel Mechanical Tubes

Grade	Condition	MPa Tensile Point	Yield Point	Elongation
	CW	≥414	≥483	≥5%
1020	SR	≥345	≥448	≥10%
	А	≥193	≥331	≥30%
	N	≥234	≥379	≥22%

Manufacturing Carbon Steel Pipes & Tubes in ASTM A519 Grade 1020

ASTM A519 1020 Straight Tubing
Chrome Moly Steel A519 1020 U Bend Tubing
Seamless ASTM A519 1020 Hydraulic Tubing
A519 1020 Steel Seamless Boiler Tubing
Seamless Black 1020 Chrome Alloy Steel CDW Tube
A519 Gr 1020 Cold Drawn Tubing
A519 Dom 1020 Tubing
SA519 1020 Condenser Tubing
Thin Wall Chrome Moly Steel 1020 Cold Drawn Seamless Tubing
1020 A519 Steel finned tubing

1020 A519 Steel High Pressure Tubing	Alloy Steel A519 1020 Water Tube Boiler
A519 Square Tubing	A519 1020 Chrome Alloy Steel Superheater Tubing
Chrome Moly Steel ASTM A519 1020 Rectangular Tubing	A519 gr 1020 Coiled Tubing
A519 Grade 1020 Welded Rectangular	A519 1020 Steel Dom Tubing
ASME A519 GR.1020 Tube	Seamless Mechanical Tubing A519 1020
A519 1020 Hf Seamless Tube	A519 1020 Cd Seamless Tube
ASTM A519 Grade 1020	A519 1020 Mechanical Tubing
ASTM A519 Grade 1020 Alloy Steel Rectangular Tube	ASTM A519 Gr. 1020 Alloy Steel Seamless Tube
High Pressure ASTM A519 GR.1020 Boiler Tube	Alloy Steel Gr ASTM A519 Gr.1020 Heater Tube
ASTM A519 Grade 1020 Seamless Tube	IBR ASTM A519 Grade 1020 Tubes
ASTM A519 GR. 1020 Tubes	ASTM A519 Grade 1020 Custom Tubes
AISI ASTM A519 GR.1020 ERW Tube	ASTM A519 GR.1020 Tubes Dealer
ASTM A519 GR. 1020 Round Tube	ASME SA 519 GR.1020 Seamless Square Tube

About Metallica Metals – The Steel Pipes Factory

- Established in 1975, the Metallica Metals Group (The Steel Pipes Factory) has its operations spread across major cities in India. We are a pioneer in the stainless steel pipes, nickel alloy products, titanium products, carbon steel pipes and alloy steel pipes manufacturing and processing industry. Our products including pipe fittings, flanges, pipes, sheet plates and valves are exported to over 70 countries across the world, while in India we have supplied to even the remote areas. With over 250 tons of sale in stainless steel and carbon steel pipes every day, Metallica has emerged as a prominent vendor for many buyers in India and Overseas
- More than 3000 tons ready from stock and new production ready in just a few weeks.
- Feel free to contact us on Email: info@metallicametals.com | Tel: +91 8928722715 | +91-22-66581538, +91-22-67436694, +91-22-66109768

Our Key Products

STAINLESS STEEL & NICKEL ALLOYS **INSTRUMENTATION TUBES & FITTINGS**

Pure Nickel Alloys Monel Alloys (Ni-Cu Alloys)

Inconel (Ni-Cr-Mo) Alloys

Incoloy Alloys (Ni-Cr-Fe)

Hastelloy Alloys

Stainless Steel 304/304L

Stainless Steel 309S/309H

Stainless Steel 310/310S

Stainless Steel 316/316L

Stainless Steel 316Ti

Stainless Steel 317/317L

Stainless Steel 321/321H

Stainless Steel 347/347H

Stainless Steel 904L

Duplex Steels (UNS S32205, UNS S31803)

Super Duplex Steels (UNS S32760 / UNS

S32750)

Stainless Steel 254 SMO (UNS S31254 / 1.4547)

<u>Instrumentation Tube</u> **Hydraulic Tubing**

Seamless Tubing

Instrumentation Tube Fittings

Double Compression Tube Fittings

Precision Pipe Fittings

Needle & Guage Valves

Manifold Valves

PRODUCTS

Steel Sheet & Plate

Steel Coil & Strip

Steel Pipes

Steel Tubes

Electropolish Tube

Heat Exchanger Tubes

Steel Bars/Rods & Wire

Fasteners (Nut. Bolt. Washer)

Steel Angle Bars

Hex Steel Bars

Round Steel Bars & Rod

Flat Steel Bars

Forgings, Rings & Forged Blocks

Stainless Steel Pipe

Stainless Steel Seamless Pipe

Stainless Steel Welded Pipe

Stainless Steel Tubes

Stainless Steel Furnace Tubes

Stainless Steel Seamless Tubing

Stainless Steel Heat Exchanger Tubes

Large Diameter Pipe

Trademarks Notice

• The nickel alloy trade names, trademarks, and registered trademarks which are mentioned in this article are the property of their respective owners. Hastelloy® is a registered trademark of Haynes International. Monel®, Inconel®, Incoloy®, and are registered trademarks of Special Metals Corporation.